

# SEFCOR, INC.

<b>OPTIONS</b>	
A()	FACTORY SET ANGLE (eg. A45 = 45° angle)
AG	SILVER-PLATED ENTIRE ASSEMBLY
BP	BLANK PAD-NO HOLES IN CONTACT PAD
CCN	SUPPLIED WITH CONTACT NUTS
CNS	SUPPLIED WITH CAP NUTS
E	EXTENSION PAD
EHV	EXTRA HIGH VOLTAGE APPLICATION
ETP	ELECTRO TIN-PLATED
FF	FINISHED BOTH SIDES OF CONTACT PAD
GS	GALVANIZED STEEL HARDWARE
GR5	GRADE 5 GALV STEEL BOLT- GALV HARDWARE
H	HEAVY (EXTRA THICKNESS CONTACT PAD)
H	INTERNAL FIT WHEN SCH80 PIPE USED
HS	SUPPLIED WITH HARDWARE SHIELD
M72	STAINLESS STEEL HARDWARE WITH BRONZE NUT
MB	WITH TONGUE MOUNTING HARDWARE
P	PIN INSULATOR MOUNTING HARDWARE
RFO	RIGID FIT ONLY, BUS SUPPORTS
S	SHORT BARREL FOR COMPRESSION
SE	STATIC ELIMINATOR SPRING
SFO	SLIP FIT ONLY, BUS SUPPORT
SND	TIN-PLATED ENTIRE ASSEMBLY
SP	SPECIAL REQUIREMENT, REFER TO FACTORY
SS	STAINLESS STEEL HARDWARE
TO	SMOOTH STUD BORE - NO THREADS
T()	SPECIAL STUD THREADS (eg. T10 = 10TPI)

\*NON-STANDARD OPTIONS AVAILABLE - MEASUREMENTS SHOWN BASED ON NEMA STANDARDS.

\*\*METRIC SMOOTH, METRIC THREADED, AND OTHER SIZES ARE AVAILABLE - CONTACT FACTORY